

Application for Planning Approval

Land Use Planning and Approvals Act 1993

APPLICATION NO.

DA2024/219

LOCATION OF AFFECTED AREA

39 BRYNAFON ROAD, DROMEDARY

DESCRIPTION OF DEVELOPMENT PROPOSAL

CHANGE OF USE (TEMPORARY DWELLING TO SECONDARY DWELLING)

A COPY OF THE DEVELOPMENT APPLICATION MAY BE VIEWED AT <u>www.brighton.tas.gov.au</u> AND AT THE COUNCIL OFFICES, 1 TIVOLI ROAD, OLD BEACH, BETWEEN 8:15 A.M. AND 4:45 P.M, MONDAY TO FRIDAY OR VIA THE QR CODE BELOW. ANY PERSON MAY MAKE WRITTEN REPRESENTATIONS IN ACCORDANCE WITH S.57(5) OF THE LAND USE PLANNING AND APPROVALS ACT 1993 CONCERNING THIS APPLICATION UNTIL 4:45 P.M. ON **04/08/2025**. ADDRESSED TO THE CHIEF EXECUTIVE OFFICER AT 1 TIVOLI ROAD, OLD BEACH, 7017 OR BY EMAIL AT <u>development@brighton.tas.gov.au</u>. REPRESENTATIONS SHOULD INCLUDE A DAYTIME TELEPHONE NUMBER TO ALLOW COUNCIL OFFICERS TO DISCUSS, IF NECESSARY, ANY MATTERS RAISED.

JAMES DRYBURGH Chief Executive Officer





KING ANCILLARY 39 BRYNAFON ROAD, DROMEDARY, TAS 7030 **REVISION 3**

ARCHITECTURAL


DA-00	FRONT COVER SHEET	DA-04	ELEVATIONS
DA-01	LOCATION PLAN	DA-05	SECTION & COLOURS
DA-02	SITEPLAN	DA-06	SITE PHOTOGRAPHS
DA-03	FLOOR & ROOF PLAN	DA-07	CAP PARKING PLAN



PO BOX 306, NEW NORFOLK, TASMANIA 7000

LIC. NO.: 1318

DEVELOPMENT APPROVAL



INFORMATION:	
Reference:	CT104152/3
Classification	N3
Classification	S
ate Zone	7
Level	BAL 29
ie Area	n/a
osion Envrionment	n/a
s'	

AREA SCHEDULE:	
Site Area:	56,520 m ²
Existing House:	311.0 m ²
Existing Deck:	80.0 m ²
Proposed Shed:	288.0 m ²
ANCILLARY:	87.0 m ²
Propsed Ancillary:	54.0 m ²
Proposed Covered Patio:	27.0 m ²
Proposed Storage:	30.0 m ²

EXISTING DWELLING EXISTING SHED


DEVELOPMENT APPROVAL











rharchitecture a: PO BOX 306, NEW NORFOLK, TASMANIA 7140

m: 0448 866 391 e: roy@rharchitecture.com.au CBOS LIC. NO.: 132955139

E:\2024 Projects\24-102 - Brynafon Road\Revit\24-102 DA Brynafon Road-R2.rvt

 3
 02/07/25
 UPDATED TO SUIT COUNCIL RFI

 2
 05/12/24
 UPDATED TO COUNCIL RFI

 1
 XX/11/24
 DA APPLICATION

REV DATE DETAILS

© Copyright These drawings and the copyright therof are the property of RH Architecture and must not be used, retained or copied without the written permission of RH Architecture. Dimensions take precendence over scaling, do not measure off drawings as print sizes may vary. This dwelling is the design of Longview Design and Drafting

RH RH RH

INIT

 $\left(\begin{array}{c} \\ \end{array} \right)$

ADAM KING - CHANGE OF USE


Project Address 39 BRYNAFON ROAD, DROMEDARY, TAS 7030.














E:\2024 Projects\24-102 - Brynafon Road\Revit\24-102 DA Brynafon Road-R2.rvt

rh

CBOS LIC. NO.: 132955139

REV DATE DETAILS

INIT.

AREA SCHEDULE



24.08 m² CLASS 10A STORAGE FLOOR AREA

60.00 m² CLASS 1A ANCILLARY FLOOR AREA

26.39 m² CLASS 10A COVERED PATIO

OVERFLOW INTO OPEN SPOON DRAIN











24-102

project no:










E:\2024 Projects\24-102 - Brynafon Road\Revit\24-102 DA Brynafon Road-R2.rvt


REV DATE DETAILS


EXTERNAL FINISHES



indicated

2/07/2025 12:38:19 PM





RH RH RH

INIT



rh

a: PO BOX 306, NEW NORFOLK, TASMANIA 7140 , m: 0448 866 391 e: roy@rharchitecture.com.au CBOS LIC. NO.: 132955139

E:\2024 Projects\24-102 - Brynafon Road\Revit\24-102 DA Brynafon Road-R2.rvt

3	02/07/25	UPDATED TO SUIT COUNCIL RFI
2	05/12/24	UPDATED TO COUNCIL RFI
1	XX/11/24	DA APPLICATION

REV DATE DETAILS

© Copyright These drawings and the copyright therof are the property of RH Architecture and must not be used, retained or copied without the written permission of RH Architecture. Dimensions take precendence over scaling, do not measure off drawings as print sizes may vary. This dwelling is the design of Longview Design and Drafting

Client/ Project Name ADAM KING - CHANGE OF USE

Project Address 39 BRYNAFON ROAD, DROMEDARY, TAS 7030. -COLORBOND ROOF SHEETING

_POWDERCOATED ALUMINIUM FRAMED DOUBLE GLAZED WINDOW

EXISTING CONCRETE SLAB



JAMES HARDIE AXON CLADDING OR SIMILAR COLOUR : LIGHT GREY

APPROVA TIMBER POSTS TO COVERED AREA COLOUR: MONUMENT



SECTION & COLOURS



DA-05 sheet no.











rharchitecture

a: PO BOX 306, NEW NORFOLK, TASMANIA 7140 m: 0448 866 391 e: roy@rharchitecture.com.au CBOS LIC. NO.: 132955139

E:\2024 Projects\24-102 - Brynafon Road\Revit\24-102 DA Brynafon Road-R2.rvt

	UPDATED TO SUIT COUNCI
	UPDATED TO COUNCIL RFI
XX/11/24	DA APPLICATION

REV DATE DETAILS

RH RH RH

INIT.

© Copyright These drawings and the copyright therof are the property of RH Architecture and must not be used, retained or copied without the written permission of RH Architecture. Dimensions take precendence over scaling, do not measure off drawings as print sizes may vary. This dwelling is the design of Longview Design and Drafting

Client/ Project Name ADAM KING - CHANGE OF USE

Project Address 39 BRYNAFON ROAD, DROMEDARY, TAS 7030.




SITE PHOTOGRAPHS



project no:

DA-06 sheet no.







PO BOX 306, NEW NORFOLK, TAS 7140 ABN 36 948 393 536

02 July 2025

Dang Van Brighton Council 1 Tivoli Road Old Beach TAS 7017 Project Ref: 25-102

RE: PLANNIG PERMIT (DA2024/219) 39 BRYNAFON ROAD, DROMEDARY.

Dear Dang

Please find enclosed our response to your RFI dated 1ST May 2025.

Please provide an amended floor plan to confirm that the proposed secondary dwelling will have a gross floor area of less than 60sqm.

Advice: The current plan dated 5 December 2024 shows three storage areas that are accessible from within the proposed secondary dwelling. To address this, please consider modifying the rooms labelled "storage" by enclosing the wall facing the living area and creating an external access point. This would isolate the storerooms and reduce the floor level attributable to the secondary dwelling.

RHA RESPONSE: we have amended the floorplan to allow for the maximum 60m2 of ancillary space, and amended the room area to suit. Access is shown externally and the remaining internal door will be permanently fixed shut.

Please provide an amended site plan that clearly identifies the site coverage of each building on the property. In addition, submit detailed floor plans for both the proposed secondary dwelling and the southern outbuilding, including clear identification of any additional or extended sections.

Reason: It has been identified that both the proposed secondary dwelling and the southern outbuilding have been extended without approval. As a result, the total site coverage on the property now exceeds 400sqm, triggering the need for assessment under Clause 11.4.1 P1 of the Rural Living Zone.

RHA RESPONSE: we have amended the areas on drawing DA-01, and shown the southern outbuilding as proposed (inc. dimensions on drawing DA-02. I have also attached the manufacturers drawings for the shed.

With regard to the assessment under clause 11.4.1 P1, our response is as follows:

11.4.1 P1 The site coverage must be consistent with that existing on established properties in the area, having regard to:

(a) Topography of the Site

The site features a gently sloping terrain, which allows for development with minimal cut and fill. The proposed development has been sited on the flattest portion of the lot, minimizing the need for earthworks and preserving the natural landscape. The slope does not present a barrier to drainage or building siting, supporting a modest level of site coverage consistent with neighbouring rural living properties.

(b) Capacity of the Site to Absorb Runoff

The property has ample permeable area due to its large lot size (approx. 5.7 hectares), with the proposed site coverage comprising only a small percentage of the overall land area.

The development incorporates:

- Rainwater tanks for roof runoff,
- Adequate stormwater dispersion via existing contours, and
- No reliance on reticulated stormwater infrastructure.

This ensures that the site can comfortably absorb and manage runoff without impacting neighbouring properties or watercourses.

(c) Size and Shape of the Site

At approximately 5.69 ha, the site is significantly larger than standard residential lots, and its regular, elongated shape allows for strategic placement of buildings with generous setbacks from all boundaries. The large lot size supports more substantial buildings without leading to a visually dominant built form or compromising open space, and the site coverage remains proportionate and low-density in nature.

(d) Existing Buildings and Constraints

The site currently contains a single dwelling and several outbuildings (e.g., sheds), typical of rural living properties in the Dromedary area. The proposed development has been designed to respond to the location of existing structures, using available cleared land and avoiding conflicts with existing utilities, vegetation, or bushfire hazard areas.

(e) Need to Remove Vegetation

Minimal vegetation removal is required. The proposed development area is already cleared or previously disturbed, avoiding impacts on native vegetation or habitat. Where trees exist, they are either exotic or sparsely located, and no significant ecological values are compromised.

(f) Character of Development on Established Properties in the Area

The pattern of development in the surrounding area is characterized by:

- Low-density rural dwellings,
- Detached outbuildings, and
- Large open curtilages around buildings.

The proposed site coverage is comparable to and consistent with nearby properties, including those with similarly scaled homes, sheds, and agricultural structures. The development maintains the rural residential character of Dromedary and does not dominate the landscape or introduce urban-style density.

Conclusion

The proposed site coverage at 39 Brynafon Road complies with Clause 11.4.1 P1 by aligning with the existing pattern of development in the area. It responds appropriately to the site's characteristics, environmental constraints, and the prevailing rural living context. The performance solution ensures that the amenity, character, and environmental values of the locality are preserved.

We hope that the above provides adequate explanation to close out the RFI, if you require any further information then please contact the undersigned.

Yours faithfully

Roy Higman DIRECTOR



Steeline Hobart ABN: 75 009 543 506

Address: 1 Whitestone Drive Austins Ferry TAS 7011 Email: chris.erends@steeline.com.au Web: www.steeline.com.au Phone: 03 6249 4988 Fax: 03 6249 3838

Quotation

No: **127171** Date: 07/07/2016 Valid: 30 Days

Adam King Dromedary TAS 7030

I would like to submit the following quotation for your proposed new steel building.

Building Specifications

Building Length:	18.00m
Building Width:	6.00m
Wall Height:	5.00m
Awnings:	5.00m
Roof Pitch:	10.0°
Awning Pitch:	5.0°
Roof Sheeting:	Corrugated 0.42 BMT - Colour: Basalt
Wall Sheeting:	Steelclad 0.42 BMT - Colour: Shale Grey
Roller-Doors:	1 x Series "B" Roller-Door (3600 x 3660) - Colour (Basalt)
	2 x Series "A" Roller-Door (2700 x 2700) - Colour (Basalt)
P/A Doors:	1 x Personal Access Door (2040 x 820) - Colour (Basalt)

Quotation Amount

Kit Price including GST:

\$ 28,950.00

Conditions

- 1. Minimum 20% deposit on order.
- 2. Balance to be paid 1 week prior to delivery on site.
- 3. Standard lead time of 4 weeks.

If you wish to proceed with ordering this building, please sign and return the attached Terms and Conditions page with your deposit to the above address. You will also need to have your final colours selected at this time. Colours cannot be changed once the building is ordered.

Please phone me for any further details or information. I trust this quotation meets with your approval and look forward to assisting with your project.

Regards Steeline Hobart




Steeline Hobart ABN: 75 009 543 506


Address:1 Whitestone Drive
Austins Ferry TAS 7011Email:chris.erends@steeline.com.auWeb:www.steeline.com.au


Phone:03 6249 4988Fax:03 6249 3838

Quotation

No: **127171** Date: 07/07/2016 Valid: 30 Days









Steeline Hobart ABN: 75 009 543 506

Email:

Web:

ABN: 75 009 543 506 Address: 1 Whitestone Drive Austins Ferry TAS 7011

www.steeline.com.au

chris.erends@steeline.com.au

Phone: 03 6249 4988 Fax: 03 6249 3838

Quotation

No: **127171** Date: 07/07/2016 Valid: 30 Days

Specifications Summary

Wind Design Speed		
Wind Region	Region: A, Terrain Category: 2, Importance Level: 2	
Wind Multipliers	Md: 1.0, Mz: 0.91, Ms: 1.00, Mt: 1.00	
Design Speed	42 m/s	

Portal Frames	
End Portal Frame	C20024
Internal Portal Frame	C20024
Knee Braces	No
Apex Braces	No

* End portal frames are upgraded to internal frames for unsheeted bays or where dominant openings cover 50% of the bay.

Roof Purlins	
Purlin Type	TopHat 64mm 1.00 BMT
Purlin Spacing	584mm
Wall Girts	
Wall Girt	TopHat 64mm 1.00 BMT
Girt Spacing	910mm
Bays	
Bay Count	5
Bay Sizes	3.00m, 3.00m, 4.00m, 4.00m, 4.00m
Rain Goods	
Gutter	Quad 115 Gutter - Colour: Basalt
Barge Cap	Type 54 Barge Flashing 0.55 BMT - Colour: Basalt
(

* ShedTech and/or the consulting engineer reserve the right to alter any nominated engineering specification without further notice.

Steeline Ridge Capping - Roll Top - Colour: Basalt

Ridge Cap



Steeline Hobart

ABN: 75 009 543 506 Address: 1 Whitestone Drive

Email:

Web:

Phone: 03 6249 4988 Fax: 03 6249 3838

Quotation

No: 127171 Date: 07/07/2016 Valid: 30 Days

TERMS & CONDITIONS OF SALE

1. PAYMENT

(a) The Customer shall pay the Supplier the amount(s) stated as per payment schedule accompanying the order.

Austins Ferry TAS 7011

www.steeline.com.au

chris.erends@steeline.com.au

- (b) The Supplier is not obliged to deliver any Goods unless the Customer has paid all amounts in full.
- (c) The Customer must pay to the Supplier all debt collection costs, including any legal fees asociated with the recovery or attempted recovery of any amount due to the Supplier under the Agreement.
- (d) As the Goods for each building are made as required, any orders cancelled after order placement will not be refunded.

2. OWNERSHIP OF THE GOODS

- (a). Ownership of the Goods does not pass to the Customer until all amounts due are paid to the Supplier.
- (b) Unless payment for the Goods is made to the Supplier by due date, the Supplier, or its agents or employees, may at any time enter on to the site where the Goods are stored and remove the Goods.
- The Customer must indemnify the Supplier in respect of any claims, losses, costs or damages that the Supplier may incur as a result (c) of the Supplier taking action under clause 2(b).
 - Until the Customer has paid for the Goods;
 - (i) The Customer must not use, sell, lease, dispose, assign or encumber the Goods (by mortgage, lien, charge or otherwise) without the consent of the Supplier: and
 - (ii) The Customer must store the Goods separately in a readily identifiable state.

3. DELIVERY

- (a) The Customer will at his expense provide or cause to be provided full and clear access to the delivery site.
- Times for delivery are approximate and the Supplier can in no way be held responsible for variations to the proposed times. (b)
- Where delivery is specified to be made to a site, any additional mechanical assistance required to unload the Goods (e.g. crane, etc) (c) must be paid for and organised by the Customer.
- The Customer is to immediately notify the Supplier in writing upon discovery of any defect or shortage in the Goods. The Customer (d) is deemed to have accepted the Goods and shall not have any claim in respect of defects or shortage unless the Supplier is notified in writing within forty eight (48) hours of delivery of the Goods.

4. COUNCIL

- (a) The Customer agrees to pay any additional costs incurred should the Local Council require any changes be made to the building.
- A rejection of any building application or scope of works by the Local Council does not constitute a cancellation of the order (b) and all moneys payable by the Customer to the Supplier shall become immediately due and payable.

5. ERECTION

- (a) This contract is based on our standard engineering designs and does not allow for underground obstructions, rock, hard ground, or unstable or reactive soil conditions. The Customer agrees to pay any additional costs incurred by the Supplier in this regard.
- The Customer must provide a clear and accessible site for the building, clear of vegetation or obstruction. The site must be level to within a 100mm tolerance. The customer agrees to pay any earthworks required in preparing the site. (c) Down pipes are supplied to ground level only. It is the Customer's responsibility to handle the discharge of roof water and
- obtain any relevant Council approvals.
- (d) It is the Customer's responsibility to provide power to the construction site if required.
- (e) It is the Customer's responsibility to clean the construction site upon completion.

6. GENERAL

- (a) Minor variations in measurements from those shown in the order shall not give rise to any claim for damages or breach of Agreement.
- (b) To the extent permitted by law, the Supplier's liability with respect to the supply of defective or faulty Goods is limited to the lowest of: (i) The replacement or repair of the Goods: or
 - Payment of the costs of replacing the Goods or supplying equivalent Goods, in each case, at the Suppliers discretion. The (ii) Supplier shall not be liable for any labour costs associated with such repair or replacement.
- (c) The Customer warrants that he has carried out his own inquiries and investigations as to adequacy or suitability of the Goods for the purpose for which the Customer intends to use the Goods and the Customer has not relied on the Supplier or the supplier's employees, agents or distributors in determining the adequacy or suitability of the Goods for the Customer's purposes.
- If the Customer defaults under any term of the Agreement or these Terms & Conditions, the Supplier may terminate the Agreement and all moneys payable by the Customer to the Supplier shall become immediately due and payable.

I hereby authorise the Supplier to commence immediate order, manufacture and delivery of the building detailed in this quote. I understand that by signing this document, the order of the building becomes NON-CANCELLABLE and that I am bound by the above Terms and Conditions of Sale.

Signature

Produced by ShedTech

ONSITE WASTEWATER ASSESSMENT

39 Brynafon Road

Dromedary

April 2025



GEO-ENVIRONMENTAL

SOLUTIONS

Disclaimer: The author does not warrant the information contained in this document is free from errors or omissions. The author shall not in any way be liable for any loss, damage or injury suffered by the User consequent upon, or incidental to, the existence of errors in the information.



Investigation Details

Client:	Adam King
Site Address:	39 Brynafon Road, Dromedary
Date of Inspection:	06/11/2024
Proposed Works:	Existing
Investigation Method:	Geoprobe 540UD - Direct Push
Inspected by:	C. Cooper

Site Details

Certificate of Title (CT):	104152/3
Title Area:	Approx. 5.7 ha
Applicable Planning Overlays:	Bushfire-prone areas, Priority Vegetation
Slope & Aspect:	7° SE facing slope
Vegetation:	Mixed Flora

Background Information

Geology Map:	MRT 1:25000
Geological Unit:	Permian Sediments
Climate:	Annual rainfall 500mm
Water Connection:	Tank
Sewer Connection:	Unserviced-On-site required
Testing and Classification:	AS1547:2012



Investigation

A number of bore holes were completed to identify the distribution and variation of the soil materials at the site, bore hole locations are indicated on the site plan. See soil profile conditions presented below. Tests were conducted across the site to obtain bearing capacities of the material at the time of this investigation.

Soil Profile Summary

Depth (m)	USCS	Description
0.00 – 0.80	SM	SANDY SILT ; light greyish brown, dry loose consistency, approx. 10% gravels
0.80 – 1.5+	CL	SANDY GRAVEL; light greyish brown, dry hard consistency, low plasticity, refusal

Site Notes

Soils have developed from Permian siltstone/sandstone and have dominantly sandy textures with clay content increasing with depth. Bedrock was encountered at approx 1.5m.

Wastewater Classification & Recommendations

According to AS1547-2012 (on-site waste-water management) the natural soil is classified as **CLAY LOAM (category 4).** The proposed ancillary is currently serviced by a septic tank with two existing absorption trenches ($2 \times 20m \times 1.5m \times 0.5m$). At the time of inspection this appeared to be functioning correctly with no visible signs of failure.

The proposed change of use to an ancillary requires this system to be assessed to ensure it has the capacity to accommodate the expected wastewater load. A Design Loading Rate (DLR) of 10L/m²/day has therefore been assigned for primary treated wastewater.

The proposed two-bedroom ancillary has a calculated maximum wastewater output of 480L/day. This is based on a tank water supply and a maximum occupancy of 4 people (120L/day/person).

Using the DLR of 10L/m²/day, an absorption area of at least 48m² will be required. As the existing absorption area is approx. 60m² it has sufficient capacity to accommodate the expected wastewater flows. No further work is required.



A 100% reserve area will need to be set aside for any future wastewater requirements. There is sufficient space available on site to accommodate the reserve due to the large property size (approx. 5ha). Therefore, a formal reserve area has not been assigned.

GES will need to be notified any variation to the wastewater loading as outlined in this report.

Dr John Paul Cumming B.Agr.Sc (hons) PhD CPSS GAICD Director



GES P/L

Land suitability and system sizing for on-site wastewater management

Trench 3.0 (Australian Institute of Environmental Health)

Assessment Report

Site assessment for on-site waste water disposal

Assessment for	Adam King	Assess. Date	5-Dec-24
		Ref. No.	
Assessed site(s)	39 Brynafon Rd Dromedary	Site(s) inspected	6-Nov-24
Local authority	Brighton	Assessed by	John Paul Cumming

This report summarises wastewater volumes, climatic inputs for the site, soil characteristics and sustem sizing and design issues. Site Capability and Environmental sensitivity issues are reported separately, where 'Alert' columns flag factors with high (A) or very high (AA) limitations which probably require special consideration for system design(s). Blank spaces on this page indicate data have not been entered into TRENCH.

Wastewater Characteristics												
astewater volume (L/day) used f						(using t	he 'No. d	of bedro	oms in a	a dwelli	ng' meth	nod)
Septic tank wastew												
		lume (L										
Total nitrogen (kg/year) gener otal phosphorus (kg/year) gener												
Climatic assumptions for site		(Evapot	ranspira	ation ca	alculated u	using the	e crop fa	ctor me	thod)			
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mean rainfall (mm)	41	36	36	45	36	29	46	47	40	48	44	56
Adopted rainfall (R, mm)	41	36	36	45 38	36	29 25	46 39	47	40	48	44	56 48
Retained rain (Rr, mm) Max. daily temp. (deg. C)	35	31	31	30	31	25	39	40	34	41	37	40
Evapotrans (ET, mm)	130	110	91	63	42	29	32	42	63	84	105	126
Evapotr. less rain (mm)	95	79	60	25	11	5	-8	2	29	43	68	78
					Annual e	evapotran	spiration	less reta	ained rain	(mm) =	4	89
Soil characterisitics												
— , , ,	<u> </u>											
Texture = 0	Clayloa	am					Cate	egory =	4	Thick	(m) =	1.5
	•	am	Adop	ted LTA	NR (L/sqm	n/day) =		0,			k. (m) = water =	
dopted permeability (m/day) =	0.78		Adop	ted LTA	NR (L/sqm	n/day) =		0,			· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste	0.78 ent me	thods			NR (L/sq m All waste	,	10	Mi	in depth	(m) to v	· · /	
dopted permeability (m/day) = (0.78 ent met water t	thods to be reta	ined or	n site:	、 I	ewater w	10 ill be dis	Mi	in depth	(m) to v	· · /	
dopted permeability (m/day) = (Proposed disposal and treatme Proportion of waste	0.78 ent met water t of on-s	thods to be reta ite prima	ained or ary treat	n site: ment:	All waste	ewater w	10 ill be dis	Mi	in depth	(m) to v	· · /	
dopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method	0.78 ent me water t of on-s on-site	thods to be reta ite prima seconda	ained or ary treat	n site: ment: ment:	All waste In dual p	ewater w ourpose : d	10 ill be dis	Mi	in depth	(m) to v	· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of co The preferred method of co	0.78 ent me water t of on-s on-site ground	thods to be reta ite prima seconda seconda	ained or ary treat ary treat ary treat	n site: ment: ment: ment:	All waste In dual p In-groun	ewater w ourpose : d	10 ill be dis	Mi	in depth	(m) to v	· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of c The preferred method of c The preferred type of in-g	0.78 ent me water t of on-s on-site ground ground	thods to be reta ite prima seconda seconda seconda	ained or ary treat ary treat ary treat ary treat	n site: ment: ment: ment: ment:	All waste In dual p In-groun Trench(e	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
dopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred type of in-g The preferred type of above-g Site modifi	0.78 ent me water t of on-s on-site ground ground ications	thods to be reta ite prima seconda seconda seconda s or spe	ained or ary treat ary treat ary treat ary treat ary treat cific des	n site: ment: ment: ment: ment: signs:	All waste In dual p In-groun Trench(e None Not need	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
dopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred type of in-g The preferred type of above-g Site modifi	0.78 ent me water t of on-s on-site ground ground ications	thods to be reta ite prima seconda seconda s or spe condary	ained or ary treat ary treat ary treat ary treat ary treat cific des	n site: ment: ment: ment: ment: signs: ent sys	All waste In dual p In-groun Trench(e None Not need	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of o The preferred type of in-g The preferred type of above-g	0.78 ent me water t of on-s on-site ground ground ications	thods to be reta ite prima seconda seconda s or spe condary	ained or ary treat ary treat ary treat ary treat cific des treatm	n site: ment: ment: ment: signs: ent sys (m) =	All waste In dual p In-groun Trench(e None Not need	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred method of of The preferred type of in-go The preferred type of above-go Site modified	0.78 ent me water t of on-s on-site ground ground ications	thods to be reta ite prima seconda seconda s or spe condary	ained or ary treat ary treat ary treat ary treat cific des treatm length	n site: ment: ment: ment: signs: ent sys (m) = (m) =	All waste In dual p In-groun Trench(e None Not need tem 29 1.5 0.6	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred type of in-g The preferred type of above-g Site modifi Suggested dimensions for on-s Total dispo	0.78 ent met of on-s on-site ground round ications site sec	thods to be retained seconda seconda socondary Total rea (sq n	ained or ary treat ary treat ary treat cific des treatm length Width Depth n) requi	n site: ment: ment: ment: signs: ent sys (m) = (m) = (m) = red =	All waste In dual p In-groun Trench(e None Not need tem 29 1.5 0.6 48	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred method of The preferred type of in-g The preferred type of above-g Site modifi Suggested dimensions for on-s Total disp- comprisin	0.78 ent met of on-s pon-site ground ications site sec osal ar	thods to be retaite prima seconda seconda s or spe condary Total rea (sq n imary Ar	ained or ary treat ary treat ary treat cific des treatm length Width Depth n) requi ea (sq r	n site: ment: ment: ment: signs: ent sys (m) = (m) = (m) = red = n) of:	All waste In dual p In-groun Trench(e None Not need tem 29 1.5 0.6	ewater w ourposes d es)	10 ill be dis	Mi	in depth	(m) to v	· · /	
dopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred type of in-g The preferred type of above-g Site modifi Suggested dimensions for on-s Total dispu	0.78 ent met of on-s pon-site ground ications site sec osal ar	thods to be retaite prima seconda seconda s or spe condary Total rea (sq n imary Ar	ained or ary treat ary treat ary treat cific des treatm length Width Depth n) requi ea (sq r	n site: ment: ment: ment: signs: ent sys (m) = (m) = (m) = red = n) of:	All waste In dual p In-groun Trench(e None Not need tem 29 1.5 0.6 48	ewater w ourposes d es)	10 ill be dis	M sposed (nk(s)	in depth of on the	(m) to v	vater =	5
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of of The preferred type of in-g The preferred type of above-g Site modifi Suggested dimensions for on-s Total dispr comprisin and a Second	0.78 ent met ewater t of on-s pon-site ground ications site sec osal ar ng a Pri dary (ba	thods to be retaite prima seconda seconda s or spe condary Total rea (sq n imary Ar ackup) A	ained or ary treat ary treat ary treat ary treat cific des treat Width Depth n) requi ea (sq r rea (sq	n site: ment: ment: ment: signs: ent sys (m) = (m) = red = n) of: m) of:	All waste In dual p In-groun Trench(e Not need Not need tem 29 1.5 0.6 48 48	ewater w uurpose s d es) ded	10 ill be dis septic ta	M sposed ink(s) Suff	in depth of on the	(m) to v e site rea is a	vailable	5
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of The preferred method of The preferred type of in-g The preferred type of above-g Site modifi Suggested dimensions for on-s Total disp- comprisin	0.78 ent met ewater t of on-s pon-site ground ications site sec osal ar ng a Pri dary (ba	thods to be retaite prima seconda seconda s or spe condary Total rea (sq n imary Ar ackup) A	ained or ary treat ary treat ary treat ary treat cific des treat Width Depth n) requi ea (sq r rea (sq	n site: ment: ment: ment: signs: ent sys (m) = (m) = red = n) of: m) of:	All waste In dual p In-groun Trench(e Not need Not need tem 29 1.5 0.6 48 48	ewater w uurpose s d es) ded	10 ill be dis septic ta	M sposed ink(s) Suff	in depth of on the	(m) to v e site rea is a	vailable	5
Adopted permeability (m/day) = 0 Proposed disposal and treatme Proportion of waste The preferred method of of The preferred type of in-g The preferred type of above-g Site modifi Suggested dimensions for on-s Total dispr comprisin and a Second	0.78 ent met ewater t of on-s pon-site ground ications site sec osal ar ng a Pri dary (ba	thods to be retaite prima seconda seconda s or spe condary Total rea (sq n imary Ar ackup) A	ained or ary treat ary treat ary treat ary treat cific des treat Width Depth n) requi ea (sq r rea (sq	n site: ment: ment: ment: signs: ent sys (m) = (m) = red = n) of: m) of:	All waste In dual p In-groun Trench(e Not need Not need tem 29 1.5 0.6 48 48	ewater w uurpose s d es) ded	10 ill be dis septic ta	M sposed ink(s) Suff	in depth of on the	(m) to v e site rea is a	vailable	5



GES P/L

Land suitability and system sizing for on-site wastewater management

Trench 3.0 (Australian Institute of Environmental Health)

Site Capability Report

Site assessment for on-site waste water disposal

Assessment for	Adam King	Assess. Date	5-Dec-24
		Ref. No.	
Assessed site(s)	39 Brynafon Rd Dromedary	Site(s) inspected	6-Nov-24
Local authority	Brighton	Assessed by	John Paul Cumming

This report summarises data relating to the physical capability of the assessed site(s) to accept wastewater. Environmental sensitivity and system design issues are reported separately. The 'Alert' column flags factors with high (A) or very high (AA) site limitations which probably require special consideration in site acceptability or for system design(s). Blank spaces indicate data have not been entered into TRENCH.

				Confid	Limit	ation	***************************************
Alert	Factor	Units	Value	level	Trench	Amended	Remarks
	Expected design area	sq m	5,000	V. high	Very low		
	Density of disposal systems	/sq km	5	Mod.	Very low		
	Slope angle	degrees	7	High	Low		
	Slope form	Straight si	mple	High	Low		
	Surface drainage	Mod.	good	High	Low		
	Flood potential Site I	loods <1:10	00 yrs	High	Very low		
	Heavy rain events	Infred	quent	High	Moderate		
Α	Aspect (Southern hemi.)	Faces SE c	or SW	V. high	High		
	Frequency of strong winds	Com	nmon	High	Low		
	Wastewater volume	L/day	480	High	Low		
	SAR of septic tank effluent		1.2	High	Low		
	SAR of sullage		2.1	High	Moderate		
	Soil thickness	m	1.5	V. high	Very low		
	Depth to bedrock	m	1.5	Mod.	Moderate		
	Surface rock outcrop	%	0	V. high	Verylow		
	Cobbles in soil	%	0	V. high	Very low		
	Soil pH		7.0	High	Very low		
	Soil bulk density gr	n/cub.cm	1.5	High	Low		
	Soil dispersion Eme	erson No.	7	V. high	Verylow		
	Adopted permeability	m/day	0.78	Mod.	Moderate		
	Long Term Accept. Rate L/	day/sq m	10	High	Low		

To enter comments, click on the line below 'Comments'. (This yellow-shaded box and the buttons on this page will not be printed.)

Comments

The site has the capability to accept onsite wastewater



GES P/L

Land suitability and system sizing for on-site wastewater management

Trench 3.0 (Australian Institute of Environmental Health)

Environmental Sensitivity Report Site assessment for on-site waste water disposal

Assessment for	Adam King	Assess. Date	5-Dec-24
		Ref. No.	
Assessed site(s)	39 Brynafon Rd Dromedary	Site(s) inspected	6-Nov-24
Local authority	Brighton	Assessed by	John Paul Cumming

This report summarises data relating to the environmental sensitivity of the assessed site(s) in relation to applied wastewater. Physical capability and system design issues are reported separately. The 'Alert' column flags factors with high (A) or very high (AA) limitations which probably require special consideration in site acceptability or for system design(s). Blank spaces indicate data have not been entered into TRENCH.

				Confid	Limi	itation	
Alert	Factor	Units	Value	level	Trench	Amended	Remarks
	Cation exchange capacity	mmol/100g	75	High	Moderate		
	Phos. adsorp. capacity	kg/cub m	0.5	High	High		
	Annual rainfall excess	mm	-489	High	Very low		
	Min. depth to water table	m	5	High	Very low		
	Annual nutrient load	kg	2.3	High	Very low		
	G'water environ. value	Agric non-s	ensit	V. high	Low		
	Min. separation dist. requir	ed m	2	High	Very low		
	Risk to adjacent bores	Ver	rylow	V. high	Very low		
	Surf. water env. value	Agric non-s	ensit	V. high	Low		
	Dist. to nearest surface wa	ter m	300	V. high	Low		
	Dist. to nearest other featu	re m	100	V. high	Low		
	Risk of slope instability	Ve	rylow	V. high	Very low		
	Distance to landslip	m	200	V. high	Low		

To enter comments, click on the line below 'Comments'. (This yellow-shaded box and the buttons on this page will not be printed.)

Comments



Disclaimer

This Report has been prepared in accordance with the scope of services between Geo-Environmental Solutions Pty. Ltd. (GES) and the Client. To the best of GES's knowledge, the information presented herein represents the client's requirements at the time of printing of the Report. However, the passage of time, manifestation of latent conditions or impacts of future events may result in findings differing from that discussed in this Report. In preparing this Report, GES has relied upon data, surveys, analyses, designs, plans and other information provided by the Client and other individuals and organisations referenced herein. Except as otherwise stated in this Report, GES has not verified the accuracy or completeness of such data, surveys, analyses, designs, plans and other information.

The scope of this study does not allow for the review of every possible geotechnical parameter or the soil conditions over the whole area of the site. Soil and rock samples collected from the investigation area are assumed to be representative of the areas from where they were collected and not indicative of the entire site. The conclusions discussed within this report are based on observations and/or testing at these investigation points.

This report does not purport to provide legal advice. Readers of the report should engage professional legal practitioners for this purpose as required.

No responsibility is accepted for use of any part of this report in any other context or for any other purpose by a third party.



AS1547:2012 – Loading Certificate – Septic System Design

This loading certificate sets out the design criteria and the limitations associated with use of the system.

Site Address: 39 Brynafon Rd, Dromedary

System Capacity: 480L/day

Summary of Design Criteria

DLR: $10L/m^2/day$.

Absorption area: 48m²

Reserve area location /use: Not assigned – more than 100% available

Water saving features fitted: Standard fixtures

Allowable variation from design flows: 1 event @ 200% daily loading per quarter

Typical loading change consequences: Expected to be minimal due to capacity of system and site area (provided loading changes within 25% of design)

Overloading consequences: Continued overloading may cause hydraulic failure of the absorption area and require upgrading/extension of the area. Risk considered acceptable due to visible signs of overloading and owner monitoring.

Underloading consequences: Lower than expected flows will have minimal consequences on system operation unless the house has long periods of non occupation. Under such circumstances additional maintenance of the system may be required. Risk considered acceptable.

Lack of maintenance / monitoring consequences: Issues of underloading/overloading and condition of the absorption area require monitoring and maintenance, if not completed system failure may result in unacceptable health and environmental risks. Septic tank de-sludging must also be monitored to prevent excessive sludge and scum accumulation. Monitoring and regulation by the property owner required to ensure compliance.

Other operational considerations: Owners/occupiers must be aware of the operational requirements and limitations of the system, including the following; the absorption area must not be subject to traffic by vehicles or heavy stock and should be fenced if required. The absorption area must be kept with adequate grass cover to assist in evapotranspiration of treated effluent in the absorption trenches. The septic tank must be desludged at least every 3 years, and any other infrastructure such as septic tank outlet filters must also be cleaned regularly (approx. every 6 months depending upon usage). Foreign materials such as rubbish and solid waste must be kept out of the system.

CERTIFICATE OF THE RESPONSIBLE DESIGNER

Section 94 Section 106 Section 129 Section 155

To:	Adam King	Owner name	25	
	39 Brynafon Road	Address	Form 35	
	Dromedary	7030	Suburb/postcode	•
Designer detail	S:			
Name:	John-Paul Cumming		Category:	Bld. Srvcs. Dsgnr Hydraulic
Business name:	Geo-Environmental Solutions		Phone No:	03 6223 1839
Business address:	29 Kirksway Place]	
	Battery Point	7004	Fax No:	N/A
Licence No:	CC774A Email address:	office@geose	olutions.net.au	
Details of the p	roposed work:			
Owner/Applicant	Adam King		Designer's proje reference No.	^{ct} J11080
Address:	39 Brynafon Road		Lot No:	104152/3
	Dromedary	7030]	
Type of work:	Building work	F	Plumbing work	X (X all applicable)
Description of wor	rk:			
On-site wastewater	management system - design		ad re- wa stc on	ew building / alteration / dition / repair / removal / erection ater / sewerage / ormwater / -site wastewater anagement system /

Description of the Design Work (Scope, limitations or exclusions): (X all applicable certificates)

Certificate Type:	Certificate		Responsible Practitioner		
	☐ Building design		Architect or Building Designer		
	☐ Structural design		Engineer or Civil Designer		
	☐ Fire Safety design		Fire Engineer		
	☐ Civil design		Civil Engineer or Civil Designer		
	🗷 Hydraulic design		Building Services Designer		
	☐ Fire service design		Building Services Designer		
	Electrical design		Building Services Designer		
	Mechanical design		Building Service Designer		
	□ Plumbing design		Plumber-Certifier; Architect, Building Designer or Engineer		
	☐ Other (specify)				
Deemed-to-Satisfy:		Performance Solution: (<i>X the appropriate box</i>)			
Other details:					
Existing dual-purpose septic tank with onsite aborption to remain without change					
Design documents	provided:				

The following documents are provided with this Certificate -

Document description: Date: Apr-25 Drawing numbers: Prepared by: Geo-Environmental Solutions Schedules: Prepared by: Date: Prepared by: Geo-Environmental Solutions Specifications: Date: Apr-25 Computations: Prepared by: Date: Performance solution proposals: Prepared by: Date: Prepared by: Geo-Environmental Solutions Test reports: Date: Apr-25

Standards, codes or guidelines relied on in design
process:
AS1547:2012 On-site domestic wastewater management.
AS3500 (Parts 0-5)-2013 Plumbing and drainage set.

Any other relevant documentation:

Onsite Wastewater Assessment - 39 Brynafon Road Dromedary - Apr-25

Onsite Wastewater Assessment - 39 Brynafon Road Dromedary - Apr-25

Attribution as designer:

I John-Paul Cumming, am responsible for the design of that part of the work as described in this certificate;

The documentation relating to the design includes sufficient information for the assessment of the work in accordance with the *Building Act 2016* and sufficient detail for the builder or plumber to carry out the work in accordance with the documents and the Act;

This certificate confirms compliance and is evidence of suitability of this design with the requirements of the National Construction Code.

	Name: (print)	Signed	Date
Designer:	John-Paul Cumming	J	08/04/2025
Licence No:	CC774A		

Assessment of Certifiable Works: (TasWater)


Note: single residential dwellings and outbuildings on a lot with an existing sewer connection are not considered to increase demand and are not certifiable. If you cannot check ALL of these boxes, LEAVE THIS SECTION BLANK. TasWater must then be contacted to determine if the proposed works are Certifiable Works. I confirm that the proposed works are not Certifiable Works, in accordance with the Guidelines for TasWater CCW Assessments, by virtue that all of the following are satisfied: x The works will not increase the demand for water supplied by TasWater The works will not increase or decrease the amount of sewage or toxins that is to be removed by, х or discharged into, TasWater's sewerage infrastructure х The works will not require a new connection, or a modification to an existing connection, to be made to TasWater's infrastructure x The works will not damage or interfere with TasWater's works x The works will not adversely affect TasWater's operations x The work are not within 2m of TasWater's infrastructure and are outside any TasWater easement x I have checked the LISTMap to confirm the location of TasWater infrastructure If the property is connected to TasWater's water system, a water meter is in place, or has been Х applied for to TasWater.

Certification:

I John-Paul Cumming....... being responsible for the proposed work, am satisfied that the works described above are not Certifiable Works, as defined within the *Water and Sewerage Industry Act 2008,* that I have answered the above questions with all due diligence and have read and understood the Guidelines for TasWater CCW Assessments.

Note: the Guidelines for TasWater Certification of Certifiable Works Assessments are available at: <u>www.taswater.com.au</u>

	Name: (print)	Signed	Date
Designer:	John-Paul Cumming	J	08/04/2025
LED PROFES			







GEO-ENVIRONMENTAL

S O L U T I O N S 29 Kirksway Place, Battery Point T| 62231839 E| office@geosolutions.net.au



1:300 @ A3

Sheet 1 of 1 Drawn by: SR